

Pillar Mechanical Packing

Style No. 6527L

- ***Braided Packing designed for use in high temperature pump applications***
- ***Extremely flexible carbon fiber packing in a single-spool packing with better chemical resistance***
- ***Excellent heat resistance and capable of long wear life***



Pillar style No. 6527L packing consists of carbon fibers interlock braided and processed with a special lubricant.



PILLAR
Engineered Sealing Solutions

GPLC 1224-1

Pillar Mechanical Packing

Style No. 6527L



Dimensions

SIZE		LOT Meter/spool (+/-10%)	Spool Size (mm)	Reference		
				ft/spool (+/-10%)	WEIGHT*	
Inches	mm			lbs	kg	
3/8"	9.5	20	φ200	65.6	4.40	2.0
		30	φ250	98.4	6.60	3.0
7/16"	11.1	20	φ250	65.6	6.00	2.7
1/2"	12.7	10	φ200	32.8	3.90	1.8
		20	φ250	65.6	7.80	3.6
5/8"	15.9	10	φ250	32.8	6.10	2.8
		20	φ300	65.6	12.20	5.6

* Product weigh (Not include spool & Box)

Specification

pH

0 to 14 (except strong oxidizers)

Temperature

~ 660°F (~ 350°C) *

Pressure

230psi (16 bar)

Shaft speed

2000fpm (10 m/s)

PV

140psi · fpm

Application

- 1) Refinery, Petro-chemical
- 2) Chemical plant
- 3) Strong acid / alkali.
- 4) Hot water, etc.

Follow the instructions, before installation and operation, for your safety.

* Specifications and dimensions are subject to change without prior notice.

* The data on this catalogue are solely for your reference and are not to be construed as constituting a warranty.

* EDP® and PILLARFOIL® are registered trademark of Nippon Pillar Packing Co., Ltd

NIPPON PILLAR PACKING CO., LTD.

11-48,2-Chome, Nonaka Minami,
Yodogawa-ku, Osaka, 532-0022 Japan
TEL +81 6 6305 2821
FAX +81 6 6302 3300
(URL) <http://www.pillar.co.jp>

DISTRIBUTED BY

